




AMMARI™

NEW



COLOR REFRACTIVE INDEX
80
REFLECTOR BEAM
24° / 40°



AMARI BASIC WHITE

LED [N] 6W CRI 80
3000K - 540lm / 5700K-603
73mm
D81 x H80 mm

5501 96 3390 01

COB [F] 9W CRI 80
3000K - 810lm / 6000K-900lm
90mm
D103x H90 mm

5501 96 3390 02

LED [N] 6W CRI 80 DIMMABLE
3000K - 540lm / 5700K-603
73mm
D81 x H80 mm

5501 96 3390 03

COB [F] 9W CRI 80 DIMMABLE
3000K - 810lm / 6000K-900lm
90mm
D103x H90 mm

5501 96 3390 04



AMARI BASIC BLACK

LED [N] 6W CRI 80
3000K - 510lm / 5700K-591
73mm
D81x H80 mm

5501 96 3491 01

COB [F] 9W CRI 80
3000K - 680lm / 6000K-730lm
90mm
D103x H90 mm

5501 96 3491 02

LED [N] 6W CRI 80 DIMMABLE
3000K - 510lm / 5700K-591
73mm
D81x H80 mm

5501 96 3491 03

COB [F] 9W CRI 80 DIMMABLE
3000K - 680lm / 6000K-730lm
90mm
D103x H90 mm

5501 96 3491 04

III 0.3 CE Ip44

REQUIREMENTS
PSU INTERNAL
CONNECTED POWER SUPPLY
180 ~ 230 VAC

III 0.3 CE Ip44

REQUIREMENTS
PSU INTERNAL
CONNECTED POWER SUPPLY
180 ~ 230 VAC